


100m eARC/ARC Over CAT


Description

Our CAT100EARC Audio over CAT cable extender transmits HDMI eARC/ARC or optical digital audio signals up to a distance of 200m (eARC/ARC signals up to 100m).

This plug and play device supports CEC pass-through when HDMI eARC/ARC audio is selected and features a built in DAC to convert either of the inputs to a stereo left / right audio output.







Key Features

- Extend either eARC/ARC or optical digital audio signals over a single CAT cable*
- CAT100EARC supports eARC/ARC distribution distances of up to 100m
- CAT100EARC supports Optical audio distribution distances of up to 200m
- Built in DAC (Digital to Analogue audio Converter) converts either HDMI eARC/ARC or optical digital to analogue stereo left/right audio output (2ch PCM only)*
- Supports CEC pass-through when HDMI eARC/ARC mode selected
- Supports bitstream passthrough of multichannel surround sound including object-based audio formats in line with HDMI specifications.
- Bi-directional PoC (Power over Cable) to power extenders from either the transmitter or receiver

Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.

 $^{^{}f{\star}}$ Selection between HDMI eARC/ARC or Optical digital audio via dipswitch on the TX







Connectivity - TX

- Audio Input Connectors: 1x Optical (SPDIF) & 1x HDMI Type A
- Output Connectors: 1x RJ45
- Firmware Upgrade: 1x Micro-USB

Connectivity - RX

- Input Connectors: 1x RJ45 & 5V/1A DC
- Output Connectors: 1x Optical (SPDIF), 1x HDMI Type A & 1x Analogue audio L/R (3.5mm stereo jack)
- Firmware Upgrade: 1x Micro USB

Specifications

- Power Supply: 24V/1.25A DC
- Dimensions (W x D x H): 74mm x 80mm x 24mm (TX/RX)
- Shipping Weight: 0.7kg (TBC)
- Operating Temperature: 32°F to 104°F (-5°C to +55°C)
- Storage Temperature : -4°F to 140°F (-25°C to +70°C)

Included Accessories

Power Supply	1 x 24V/1.25A DC
Mount	1 x Mounting Kit

Regulatory Compliance















Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.